



MODEL: 1999-H Underground Tank

Engineering and design data:

Pressure vessel designed to A.S.M.E. code LPG service.
 National Board certification available upon request (included for U.S. tanks).
 Tank volume: 1999 USWG (at 100%)
 Design pressure: 250 psi at 115°F
 Hydrostatic test: 325 psi
 Outside surface area: 295 sq.ft.
 Head form: Semi-Elliptical
 Head material: SA-455 Thickness: 0.282" min.
 Shell material: SA-455 Thickness: 0.343" min.
 Tank weight (empty): 4 500 lbs.
 All materials made in the U.S.A.
 Tanks manufactured in Canada.

PRO-PAR INC.
 65 Winder,
 Sherbrooke QC, Canada
 J1M 1L6
 TEL.: 819-566-8211
 FAX.: 819-821-2513



MODEL: 1999-H STANDARD TANK				
NOZZLE	ITEM #	QTY.	DESCRIPTION	SERVICE
N1	-	1	2-1/2" MNPT PIPE	CLUSTER VALVE / FLOAT GAUGE
N2	-	1	1-1/4" NPT COUPLING	LIQUID OUTLET
N3	-	1	1-1/4" NPT COUPLING	SPARE
-	1	1	SHROUD	-
-	2	2	LIFTING LUGS	-
-	3	2	LEGS 1/4" THK. X 6" WIDE	-
-	4	1	PRO-PAR INC. NAMEPLATE - SS304	-