



MODEL: 320-H UNDERGROUND TANK (US)

Engineering and design data:

Pressure vessel designed to A.S.M.E. code LPG service.
 National Board certification available upon request (included for U.S. tanks).
 Tank volume: 320 USWG (at 100%)
 Design pressure: 250 psi at 155°F
 Hydrostatic test: 325 psi
 Outside surface area: 77 sq.ft.
 Head form: Hemispherical
 Head material: SA-414C Thickness: 0.148" min.
 Shell material: SA-455 Thickness: 0.216" min.
 Tank weight (empty): 675 lbs.
 All materials made in the U.S.A.
 Tanks manufactured in Canada

MODEL: 320-H UNDERGROUND TANK				
NOZZLE	ITEM #	QTY.	DESCRIPTION	SERVICE
N1	-	1	2-1/2" MNPT PIPE	CLUSTER VALVE / FLOAT GAUGE
N2	-	1	3/4" NPT COUPLING / RISER PIPE	LIQUID OUTLET
N3	-	1	1-1/4" NPT COUPLING	DRAIN
-	1	1	SHROUD	-
-	2	2	LIFTING LUGS	-
-	3	2	LEGS 1/4" THK. X 3" WIDE	-
-	4	1	PRO-PAR INC. NAMEPLATE - SS304	-