

A complete range, for every need

The steel cylinders and tanks offered by Mazout & Propane Beauchemin are designed for temporary heating, propane appliance supply and any other outdoor application. From the 100 lb portable cylinder to the 1,000 gal tank, we offer the right solution for your project.



100 lb DOT
46.6 in × 15.1 in
POL or multi-valve



28.6 gal ASME "Mini"
37.1 in × 18 in
Compact format



200 lb DOT / 57 gal ASME
41.9 in × 24 in
Versatile format



420 lb DOT / 118 gal ASME
53.8 in × 30 in
Large format

Feature	100 lb DOT <i>POL valve</i>	100 lb DOT <i>multi-valve</i>	200 lb DOT	420 lb DOT	28.6 gal ASME <i>"Mini"</i>	57 gal ASME	118 gal ASME
CAPACITY							
LPG capacity	22.9 gal 87 L	22.9 gal 87 L	45.6 gal 172.9 L	95.9 gal 363 L	22.9 gal 86.6 L	45.6 gal 172.9 L	95.9 gal 363 L
Water capacity	238 lb 108 kg	238 lb 108 kg	476 lb 216 kg	1,000 lb 450 kg	28.5 gal 108.3 kg	57 gal 216 kg	118 gal 450 kg
DIMENSIONS							
Overall height	46.6 in 1,184 mm	46.6 in 1,184 mm	41.9 in 1,064 mm	53.8 in 1,366 mm	37.1 in 942 mm	41.9 in 1,064 mm	53.8 in 1,366 mm
Body height	41 in 1,041 mm	41 in 1,041 mm	34.1 in 865 mm	45.6 in 1,159 mm	29.8 in 756 mm	34.1 in 865 mm	45.6 in 1,159 mm
Cylinder diameter	15.1 in 383 mm	15.1 in 383 mm	24 in 610 mm	30 in 762 mm	18 in 457 mm	24 in 610 mm	30 in 762 mm
Base diameter	14 in 356 mm	14 in 356 mm	20 in 508 mm	23.1 in 587 mm	15.5 in 394 mm	20 in 508 mm	23.1 in 587 mm
Tare weight	71 lb 31.8 kg	71 lb 31.8 kg	152 lb 85.3 kg	278 lb 126.1 kg	85 lb 38.6 kg	188 lb 85.3 kg	291 lb 132 kg
CONFIGURATION							
Standard	4BW240	4BW240	4BW240	4BW240	ASME	ASME	ASME
Valve	POL (vapor or liquid)	Multi-valve	CGA-510	CGA-510	CGA-510	CGA-510	CGA-510
Sight gauge	—	—	Yes	Yes	Yes	Yes	Yes
Color	DOT gray / TC white	DOT gray / TC white	White	White	White	White	White
Quantity per pallet	18	18	16	9	20	16	9

TECHNICAL FEATURES

- **TC/DOT** cylinders can be transported filled up to **80% of total volume**. **ASME** tanks, up to a maximum of **5%**.
- **DOT re-inspection period: 12 years** after manufacture, then every **5 years** thereafter.
- **TC re-inspection period: every 10 years**.
- The **ASME** code requires **no** re-inspection period.
- **Carbon steel** construction with powder coating for optimal rust protection.
- The 200 lb and 420 lb tanks are **vacuum-purged** to reduce commissioning time and cost.
- More robust material for **strength, protection and long service life**.
- **Oversized lifting lugs** to accommodate heavy-duty lifting hooks on the **200 lb and 420 lb** models.
- Collar and valves oriented to facilitate **manifold connection**.
- Liquid level valve port **no. 54**.
- **HDPE** (high-density polyethylene) covers are durable, rustproof and impact-resistant — **10-year warranty**. Steel covers available on request.
- Designed for **aboveground** use.

CODES & CERTIFICATIONS

- Cylinders comply with **Department of Transportation (DOT)** and **Transport Canada (TC)** requirements.
- Tanks designed and manufactured according to the latest edition of the **ASME Code, Section VIII, Division I**.
- Registered with the **National Board of Boiler and Pressure Vessel Inspectors**.
- Compliant with **NFPA 58** (Liquefied Petroleum Gas Code).
- Compliant with **Railroad Commission of Texas** specifications.
- Registered with **CRN** (Canadian Registration Number) for use in Canada.

A question, a quote or a delivery? Our team is at your service:

514 990-1901 info@mpbeauchemin.com