



**2000-H DISPENSER TANK (US)**

MARK	#	QTY	DESCRIPTION	SERVICE
-	1	1	16" DOME COVER - FLAT	-
-	2	2	PHOENIX LIFTING LUG #2-900	-
-	3	2	PL 1/4" (LEG)	-
-	4	1	PRO-PAR INC. NAMEPLATE	-
N1	5	1	1 1/4" NPT COUPLING PHOENIX #506	FILLER VALVE
N2	6	1	3/4" NPT COUPLING PHOENIX #504	SERVICE
N3	7	1	JUNIOR FLOAT GAUGE ADAPTOR PHOENIX #821	FLOAT GAUGE
N4	8	1	1 1/4" NPT COUPLING PHOENIX #506	VAPOR
N5	9	1	1 1/4" NPT COUPLING PHOENIX #506	SAFETY RELIEF VALVE
N6	10	1	1" NPT COUPLING PHOENIX #505	SAFETY RELIEF VALVE
N7	11	1	1 1/4" NPT COUPLING PHOENIX #506	DRAIN
N8	12	1	1 1/4" NPT COUPLING PHOENIX #506	LIQUID
N9	13	1	3/4" NPT PHOENIX #506-S C/W RISER 46"LG	VAPOR
N10	14	1	3/4" NPT PHOENIX #506-S C/W RISER 46"LG	VAPOR
N11	15	1	1 1/4" NPT COUPLING PHOENIX #506	LIQUID

**MODEL: P4800P008 - 2000-H DISPENSER TANK (US)**

**ENGINEERING AND DESIGN DATA :**

PRESSURE VESSEL DESIGNATED TO A.S.M.E. CODE LPG SERVICE.  
NATIONAL BOARD CERTIFICATION AVAILABLE UPON REQUEST (INCLUDED FOR U.S. TANKS)  
Tank volume: 1999 USWG (AT 100%)  
DESIGN PRESSURE: 250/-12 PSI AT 115°F  
Hydrostatic test : 325 PSI AT 50°F  
Outside surface area: 295 SQ. FT.  
Head form: SE 2:1  
Head material: SA-455  
Shell material: SA-455  
TANK WEIGHT (EMPTY): 3 650 LBS  
TANKS MANUFACTURED IN CANADA

THICKNESS: 0.280" MIN.  
THICKNESS: 0.290" MIN.